


“Light” Restoration Glass® | “Antique” Window Glass



Application:

Interior, Exterior

Composition:

Glass

Installation:

See installation instructions at www.restorationglass.com/how-to-install.cfm. For laminated Restoration Glass®:

- Use only Neutral Cure Silicone Sealants.
- All gaskets, glazing materials, setting blocks, etc. must be compatible.
- Use only approved structural glazing.
- Do not use acid based sealants.
- Do not use solvent-base primers or other products prior to applying sealants.
- Do not use neoprene setting blocks.
- Do not use cleaners containing hydrocarbon solvents.

Approx Dimensions:

Cut-to-size; approx. max. size = 32" x 37" (0.8 m x 0.9 m); approx. thickness for standard non-safety glass = 3/32" (2 mm) / laminated = 1/4" (6 mm); available in larger thicknesses through lamination

Approx Weight:

1.5 lbs/ft² (7.3 kg/m²) monolithic or 3 lb/ft² (14.5 kg/m²) laminated

Safety Options:

Standard, Laminated

Maintenance:

Bendheim glass is easy to maintain. We suggest cleaning with warm water and a lint free cloth (terry cloth). Conventional non-abrasive glass cleaners may also be used.

Testing:

Laminated Restoration Glass® is safety glass, meeting the requirements for ANSI Z97.1 & the Consumer Product Safety Commission CPSC 16FR, Part 1201 – Safety Standard for Architectural Glazing Materials.

Potential Leed Credit:

- IEQ Credit 8.1: Daylight & Views: Daylight 75% of Spaces
- IEQ Credit 8.2: Daylight & Views: Views for 90% of Spaces

Options & Customizations:

- "Full" Restoration Glass® - slightly more pronounced antique character, matches antique window glass of the 17th and 18th centuries
- Restoration Mirror™ (mirrored version)

Image not found or type unknown



Image not found or type unknown

