

## Soft-Etched Back-Painted Glass | Ultra-White or Any Color



### Application:

Interior

### Composition:

Low-iron glass and specialty isocyanate-free color coatings (a VOC-free product)

### Installation:

Neutral cure silicones, in conjunction with mechanical fasteners to support the weight of the glass.

### Approx Dimensions:

Cut-to-size; max. size and thickness depend on application, up to 60" x 120" (1.5 m x 3 m); thicknesses: 1/8" (3mm), 1/4" (6mm), and 3/8" (10mm); larger sizes and thicknesses available by special order

### Approx Weight:

Varies by thickness; ranges approx. 1.5 lb/ft<sup>2</sup> (7.5 kg/m<sup>2</sup>) to 5 lb/ft<sup>2</sup> (24.5 kg/m<sup>2</sup>) for monolithic glass

### Safety Options:

Standard, Tempered, Laminated

## Maintenance:

Bendheim glass is easy to maintain. We suggest cleaning with warm water and a lint free cloth (terry cloth). Conventional non-abrasive glass cleaners may also be used.

## Testing:

Bendheim safety glass meets the requirements for ANSI Z97.1 & the Consumer Product Safety Commission CPSC 16FR, Part 1201 – Safety Standard for Architectural Glazing Materials.