

## “Forest Green” Colored Architectural Glass

---



### Application:

Interior, Exterior

### Composition:

Low-iron glass

### Approx Dimensions:

Cut-to-size; max. size = 60" x 120" (1.5 m x 3 m); thickness = 5/16" (8 mm). Available in thicknesses up to 3/4" (19 mm) by special request.

### Approx Weight:

4 lb/ft<sup>2</sup> (19.5 kg/m<sup>2</sup>)

### Safety Options:

Laminated

### Maintenance:

Bendheim glass is easy to maintain. We suggest cleaning with warm water and a lint free cloth (terry cloth). Conventional non-abrasive glass cleaners may also be used.

## Testing:

Bendheim safety glass meets the requirements for ANSI Z97.1 & the Consumer Product Safety Commission CPSC 16FR, Part 1201 – Safety Standard for Architectural Glazing Materials.

## Potential Leed Credit:


- EA Credit 1: Optimize Energy Performance
- IEQ Credit 8.1: Daylight & Views: Daylight 75% of Spaces
- IEQ Credit 8.2: Daylight & Views: Views for 90% of Spaces

## Options & Customizations:

A wide range of custom colors & opacities:



Light-diffusing etched and textured surface options available:



Laminated to

mirror for wall cladding applications Have a project requiring further customization? Please contact your local Bendheim representative to discuss your unique project and vision.