

Back-Painted Glass in Soft Bluish-Green “Pale Green #1”



Application:

Interior

Composition:

Low-iron glass and specialty isocyanate-free color coatings (a VOC-free product)

Installation:

Neutral cure silicones, in conjunction with mechanical fasteners to support the weight of the glass.

Approx Dimensions:

Cut-to-size; max. size = 60" x 120" (1.5 m x 3 m); thicknesses ranging from 1/8" (3 mm) to 1/2" (12 mm). Larger sizes and 3/4" thickness available by special request.

Approx Weight:

Varies by thickness; ranges approx. 1.6 lb/ft² (8 kg/m²) to 6.5 lb/ft² (32 kg/m²) for monolithic (not laminated) glass

Safety Options:

Standard, Tempered, Laminated

Maintenance:

Bendheim glass is easy to maintain. We suggest cleaning with warm water and a lint free cloth (terry cloth). Conventional non-abrasive glass cleaners may also be used.

Testing:

Bendheim safety glass meets the requirements for ANSI Z97.1 & the Consumer Product Safety Commission CPSC 16FR, Part 1201 – Safety Standard for Architectural Glazing Materials.

Options & Customizations:

- Unlimited custom color options, including metallics
- Light-diffusing etched and textured surface options available
- Laminated to another back-painted glass; Ex.: one side of the laminated glass may be "Pale Green 1", the other side "Khaki Off-White"
- Have a project requiring further customization? Please contact your local Bendheim representative to discuss your unique project and vision.