BENDHEIM

Bendheim Corporate
82 Totowa Road, Wayne, NJ 07470

Phone: 800.221.7379
info@bendheim.com

“Clear Fibers” Laminated Architectural Glass



Application:

Interior

Composition:

Glass; decorative translucent fibrous interlayer

Approx Dimensions:

Cut-to-size; max. size = 59" x 120" (1.5 m x 3.0 m); thickness = 1/4" (8 mm). Available in larger sizes and thicknesses up to 3/4" (19 mm) by special request.

Approx Weight:

3 lb/ft² (14.5 kg/m²)

Safety Options:

Laminated, Tempered_laminated

Maintenance:

Bendheim glass is easy to maintain. We suggest cleaning with warm water and a lint free cloth (terry cloth). Conventional non-abrasive glass cleaners may also be used.

Bendheim Corporate
82 Totowa Road, Wayne, NJ 07470

Phone: 800.221.7379
info@bendheim.com

Testing:

Bendheim laminated safety glass meets the requirements for ANSI Z97.1 & the Consumer Product Safety Commission CPSC 16FR, Part 1201 – Safety Standard for Architectural Glazing Materials.

Options & Customizations:

Light-diffusing, minimally-reflective "soft-etched" surface options available. Have a project requiring further customization? Please contact your local Bendheim representative to discuss your unique project and vision.