

Low-Iron SatinTech™ Soft-Etched Architectural Glass



Application:

Interior, Exterior

Composition:

Low-iron glass

Approx Dimensions:

Cut-to-size; max. size depends on glass thickness and safety option; Width: 86" (2.2m); Height: 126" (3.25m); Thickness: 1/8" (3mm), 1/4" (6mm), and 3/8" (10mm).

Approx Weight:

Varies by thickness; ranges approx. 1.5 lb/ft² (7.5 kg/m²) to 5 lb/ft² (24.5 kg/m²) for monolithic (not laminated) glass

Safety Options:

Standard, Tempered, Laminated, Tempered_laminated

Maintenance:

Bendheim glass is easy to maintain. We suggest cleaning with warm water and a lint free cloth (terry cloth). Conventional non-abrasive glass cleaners may also be used.

Testing:

Bendheim safety glass meets the requirements for ANSI Z97.1 & the Consumer Product Safety Commission CPSC 16FR, Part 1201 – Safety Standard for Architectural Glazing Materials.

Options & Customizations:

- Laminated to mirror or back-painted in an unlimited range of colors for wall cladding applications
- Laminated with a wide range of decorative interlayers, including transparent and translucent colors
- Laminated in combination with other etched and textured glasses
- Tempered-and-laminated form for special applications