Bendheim Corporate
82 Totowa Road, Wayne, NJ 07470

Phone: 800.221.7379
info@bendheim.com

Black Fritted Rainscreen Glass

Application:

Interior, Exterior

Composition:

Glass, ceramic frit

Approx Dimensions:

Max. size = Based on design wind load. Please contact us for additional information at rainscreens@bendheim.com; thicknesses ranging from 1/4" (6 mm) to 1/2" (12 mm).

Approx Weight:

Varies by thickness; 3 to 6 lb/ft² (14.6 to 29.3 kg/m²)

Safety Options:

Tempered

Maintenance:

Bendheim glass is easy to maintain. We suggest cleaning with warm water or conventional non-abrasive glass cleaners. Installed in the smartly engineered Längle glazing clips, broken or damaged glass panels can be quickly and easily replaced without having to deglaze surrounding panels.

Bendheim Corporate
82 Totowa Road, Wayne, NJ 07470

Phone: 800.221.7379
info@bendheim.com

Testing:

Bendheim safety glass meets the requirements for ANSI Z97.1 & the Consumer Product Safety Commission CPSC 16FR, Part 1201 – Safety Standard for Architectural Glazing Materials.

Options & Customizations:

- Virtually unlimited creative design possibilities, including custom patterns, colors, low-iron, and more
- 1/2? (12 mm) glass available on special request